

TECHNICAL DETAILS

WIDTH ± 1/8" 13 1/4" 337 mm	LENGTH ± 1/4" 40" 1.02 m
EXPOSURE 5 5/8" 143 mm	GRANULE ADHESION 0.35 g Typical Results
SHINGLES/SQUARE 64 4 bundles/square	SQUARES/PALLET 11 from OR/CA/OK

TEST COMPLIANCE

ASTM D7158 Class H	ASTM D3462
ASTM D3161 Class F	ASTM D3018 Type I
ASTM E108 Class A Fire Rating	UL RATING 2218 Class 4
CSA A123.5	

FEATURES & BENEFITS

- Flexor™ SBS polymer modified asphalt
- Extreme weather protection
- Superior granular embedment
- All-weather flexibility
- Double rain seal protection
- Larger nailing area of The Zone®
- Scotchgard™ protection from 3M
- Limited Lifetime Shingle Warranty
- Limited & Enhanced Wind Warranties

HEAVYWEIGHT FLEXOR™ SBS POLYMER MODIFIED LAMINATED ARCHITECTURAL SHINGLES


PRODUCT USE

The 265 Legacy® XL shingle with Scotchgard™ is a laminated asphalt shingle fortified with Malarkey's Flexor™ SBS polymer modified asphalt technology for increased flexibility, extreme weather protection, and superior granule adhesion. Legacy® XL's increased thickness gives it a more pronounced, distinctive look and features the exclusive nailing accuracy-enhancing design of The Zone®. The larger nailing area of The Zone® dramatically improves correct fastener placement and speeds installation. Legacy® XL also features Scotchgard™ Protector from 3M for added protection against black streaks caused by algae.

COMPOSITION & MATERIALS

Legacy® XL is a self-sealing, laminated asphalt shingle manufactured on a non-woven fiberglass mat, impregnated and coated on both sides with Flexor™ SBS polymer modified asphalt compounded with a mineral stabilizer, and surfaced with algae resistant, ceramic granules. The underside of the shingle has headlap granules as a backing agent.

APPLICATION

Shingles should be applied over a Malarkey underlayment or an approved, code-compliant substitute. Installation instructions are available on the shingle wrapper, at WWW.MALARKEYROOFING.COM, or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails for this purpose. Staples are not allowed.

PRECAUTION

For best results, Malarkey recommends Legacy® XL be protected from the weather and stored in a cool, dry, well-ventilated area until applied. Do not double-stack pallets. Do not use on roofs where the slope is less than 2:12 (2" [51 mm] per 12" [305 mm]). For slopes 2:12 up to 4:12 (4" [102 mm] per 12" [305 mm]), a double layer of underlayment is required. Legacy® XL has a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. On slopes greater than 21" (533 mm) per 12" (305 mm), hand-sealing underneath and six nails are required. Contact Malarkey for further conditions and instructions.

WARRANTY

Malarkey Roofing Products® offers various warranties to meet specific requirements. The warranty packages available for Legacy® XL include a Limited Lifetime Warranty, a 110 mph (177 kph) Limited Wind Warranty, and can be combined with other Malarkey products for a 130 mph (209 kph) Enhanced Wind Warranty. Legacy® XL also carries Malarkey's Limited Lifetime Scotchgard™ Protector Warranty against algae growth and staining. Contact your roofing contractor, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Legacy® XL and other Malarkey products are available throughout North America and Pacific Rim countries. Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products® Inventory SKU number for this product: 265 Legacy® XL featuring Scotchgard™ Protector from 3M

TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available.
Contact Malarkey for details:
Call weekdays 7:00 am to 5:00 pm PST,
at 800.545.1191 or 503.283.1191.
technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217